

PERFIL TUBULAR

6

TABLAS DE PESOS Y CALIBRES

Longitud Estandar 6.00 Mts. Salvo indicación en contrario -Pesos Teóricos, con variación de $\pm 5\%$

No.	Calibre	N.	P.	KILOS			No.	Calibre	N.	P.	KILOS				
				LONG. MTS.	POR METRO	PIEZAS POR ATADO					LONG. MTS.	POR METRO	PIEZAS POR ATADO		
101	18	x	x		1.2	7.2	10	M-600	18	x	x	5.50	2.3	12.7	7
	20	x	x		0.9	5.4	10		20	x	x	5.50	1.7	9.4	7
103	18	x	x		1.5	9.0	10	M-601*	18	x	x	5.50	2.6	14.3	6
	20	x	x		1.1	6.6	10		20	x	x	5.50	2.0	11.0	6
106	18	x	x		1.5	9.0	10	M-724*	18	x	x	3.05	2.4	7.3	10
	20	x	x		1.1	6.6	10		20	x	x	3.05	1.8	5.5	10
116	20	x	x		1.5	9.0	8	M-725	18	x	x	5.50	2.7	14.9	6
119	18	x	x		1.9	11.4	5		20	x	x	5.50	2.0	11.0	6
	20	x	x		1.5	9.0	5	P-100	18	x	x		1.4	8.4	8
120	18	x	x		1.4	8.4	8		20	x	x		1.0	6.0	8
	20	x	x		1.0	6.0	8	P-150	18	x	x		1.6	9.6	8
121	18	x	x		1.4	8.4	8		20	x	x		1.2	7.2	8
	20	x	x		1.0	6.0	8	P-200	18	x	x		1.9	11.4	8
122	18	x	x		1.4	8.4	10		20	x	x		1.4	8.4	8
	20	x	x		1.0	6.0	10	P-250	18	x	x		2.1	12.6	6
123	20	x	x		1.1	6.6	10		20	x	x		1.6	9.6	6
	18	x	x		0.7	4.2	10	P-300	18	x	x		2.3	13.3	6
124	18	x	x		1.7	10.2	8		20	x	x		1.8	10.8	6
	20	x	x		1.3	7.8	8	P-400	18	x	x		2.8	16.8	4
127	18	x	x		1.9	11.4	5		20	x	x		2.1	12.6	4
	20	x	x		1.5	9.0	5	K-150	18	x	x		1.9	11.4	9
131	20	x	x		0.6	3.6	20		20	x	x	3.05	1.5	9.0	9
144	18	x	x		1.6	9.6	10	K-200	20	x	x	3.05	1.7	5.2	10
	20	x	x		1.2	7.2	10	K-300	18*	x	x	3.05	2.8	8.5	10
145	20	x	x		0.7	4.2	20		20	x			2.1	6.4	10
147	20	x	x	0.91	6.7	6.1	1	C-050	18	x			0.5	3.0	20
	20	x	x	1.83	6.7	12.3	1		20	x			0.4	2.4	20
148*	20	x	x	2.44	6.7	16.3	1	C-075	18 t.p.	x	x		0.7	4.2	20
	20	x	x	3.05	6.7	20.4	1		20 t.p.	x			0.5	3.0	20
149	Ver No. 147						C-100	14	x			1.5	9.0	10	
154	Ver No. 147							16	x			1.2	7.2	10	
154	18	x	x		0.3	1.8	50		18 t.p.	x	x		1.0	6.0	10
	20	x	x		0.2	1.2	50		20 t.p.	x	x		0.7	4.2	10

No.	Calibre	N.	P.	KILOS			No.	Calibre	N.	P.	KILOS			
				LONG. MTS.	POR METRO	POR PIEZA					LONG. MTS.	POR METRO	POR PIEZA	
155	20	x	x		0.3	1.8	50	C-125	14	x		1.9	11.4	8
156	20	x	x		0.4	2.4	25		16	x		1.5	9.0	10
160	18	x	x		1.5	9.0	10		18	x*	x	1.2	7.2	10
	20	x	x		1.1	6.6	10		20	x*	x	0.9	5.4	10
163*	20	x	x		1.1	6.6	8	C-150	12*	x		3.1	18.6	1
164*	20	x	x		1.1	6.6	10		14	x		2.3	13.8	1
165*	20	x	x		1.6	9.6	8		16	x		1.8	10.8	1
166*	20	x	x		1.7	5.2	10		18	x	x	1.5	9.0	10
169	20	x	x		1.2	7.2	10		20	x*	x	1.1	6.6	10
170	20	x	x		1.6	9.6	8	C-175 *	14	x		3.7	22.2	1
171	20	x	x		0.9	5.4	10		16	x		2.6	15.6	1
180	20	x	x		2.2	13.2	6	C-200	12	x		4.1	24.6	1
181	20	x	x		1.2	7.2	10		14	x		3.0	18.0	1
183	22	x	x		1.2	7.2	10		16	x		2.4	14.4	1
212 c/p.	24		x		0.4	0.2	50		18	x	x	1.9	11.4	8
c/p.*	24		x		0.4	0.5	50	C-250	12	x		5.2	31.2	1
s/p.*	24		x		0.4	2.5	30		14	x		3.7	22.2	1
214 c/p.*	24		x		0.4	1.7	30		16	x		3.0	18.0	1
s/p.*	24		x		0.4	2.4	30	R-050*	18	x		0.5	3.0	20
1106*	20		x		0.9	1.6	20	R-100	18	x	x	0.7	4.2	20
1108*	20		x		0.9	2.2	20	R-125	18	x*	x	1.0	6.0	10
1110*	20		x		0.9	2.7	20		20	x	x	0.7	4.2	10
1306*	18		x		1.4	2.6	20	R-175	18	x*	x	1.2	7.2	10
1308*	18		x		1.4	3.4	20		20	x*	x	0.9	5.4	10
1310*	18	x	x		1.4	4.3	20	R-200	14	x		2.3	13.8	8
1400	18	x	x		1.2	7.2	12		16*	x		1.8	10.8	8
1500	14	x			3.0	18.0	4		18	x	x	1.5	9.0	10
	16	x			2.5	15.0	4		20	x	x	1.1	6.6	10
M-138	18	x	x		1.2	7.2	12	R-225	18	x	x	1.5	9.0	10
	20	x	x		0.9	5.4	12		20	x*	x	1.1	6.6	10
M-220	18	x	x		2.0	12.0	6	R-249	18	x*	x	1.8	10.8	8
	20	x	x		1.5	9.0	6		20	x*	x	1.4	8.4	8
M-221	18	x	x		2.0	12.0	6	R-250	12	x		4.1	24.6	1
	20	x	x		1.5	9.0	6		14	x		3.0	18.0	1
M-225	18	x	x		1.4	7.7	8	R-300	14	x		3.4	20.4	1
	20	x	x		1.1	6.1	8		16	x		2.7	16.2	1
M-300	18*	x	x		1.6	8.8	8		18	x	x	2.2	13.2	6
	20	x	x		1.2	6.6	8		20	x	x	1.6	9.6	6
M-350	20	x	x		1.1	6.1	10	R-400	14	x		4.1	24.6	1

No.	Calibre	N.	P.	KILOS PIEZAS		
				LONG. MTS.	POR METRO	POR PIEZA ATADO
M-525	18*	x	x	2.1	11.6	7
	20	x	x	1.6	8.8	7

No.	Calibre	N.	P.	KILOS PIEZAS		
				LONG. MTS.	POR METRO	POR PIEZA ATADO
	16	x		3.3	19.8	1
	18	x	x	2.7	16.2	4
	20	x	x	2.0	12.0	4







